

ISIS II RECOIL DAMPER ORDER FORM

Please print and complete this form, enclose your cheque and post to the address above.

NAME:

DELIVERY ADDRESS:

TELEPHONE NO (day) POSTCODE:

..... (or evening):

EMAIL ADDRESS:

CHEQUE ENCLOSED FOR: £
(please make cheques payable to Recoil Systems)

We now accept Credit & Debit Cards
Telephone us on +44 (0) 1763 837 140
if you prefer to pay by credit/debit card.

WHICH ISIS II RECOIL SYSTEM WOULD YOU LIKE TO ORDER?

ISIS II LIGHT - STANDARD MODEL
PLEASE TICK WHICH SHOCK ABSORBER YOU WOULD LIKE FITTED TO YOUR ISIS II RECOIL DAMPER:

SOFT or MEDIUM (SEE NOTES BELOW)

ISIS II LIGHT - SEMI-AUTO MODEL (SHORT)
FOR SHORTENED SEMI-AUTO STOCKS (OVERALL MEASUREMENT WITH 11 mm GREEN PAD - 84 mm) FOR 24 - 28grm LOADS ONLY (32grm LOADS BY SPECIAL ORDER).

£228 inc. VAT without PAD

SPECIAL OFFER

BUY THE RECOIL DAMPER & GREEN PAD FOR ONLY £256 inc. VAT!
(£273 if bought separately.)
For Green Pad, please select pad thickness

- 11mm Green Pad - 14mm Green Pad

BUY THE RECOIL DAMPER & FULLY ADJUSTABLE 20mm PAD FOR ONLY £296 inc. VAT!
(£319 if bought separately)

SureFit contouring for left & right-handed shooters

Left-handed Right-handed

Prices exclude shipping. Please add £8 for shipping within mainland UK. For international shipping options and prices, please contact us at: david@recoilsystems.com or tel: +44 (0)1763 837140.

CHOICE OF SHOCK ABSORBER:

To give optimum recoil absorption there are two interchangeable shock absorbers available for the ISIS II Recoil Damper Standard Model. The shock absorbers are classified as **SOFT** and **MEDIUM**

- a) if 24grm-32grm loads are to be used, we would recommend the **SOFT** unit
- b) if 32grm-36grm loads are to be used, we would recommend the **MEDIUM** unit
- c) If the unit is to be fitted to a semi-auto, we would recommend the **SOFT** unit for 24grm-36grm loads.

PLEASE NOTE:

The damper unit allows the gun to move backwards into the shoulder by about 6mm (1/4") when the gun is fired. If your gun has a high comb, it may need to be reduced slightly to avoid contact with your cheek during recoil.

If the Standard Model is to be fitted to a semi-auto, a minimum dimension of 100mm (4") is needed between the face of the pad/butt plate and the stock bolt. This allows for a 10mm/12mm butt plate to be used.